


THE CLEAR CHOICE SINCE 1936





The Glasfloss Puracell II P & PH 6" Plastic Frame Mini-Pleat Series is designed for use in applications where a high degree of efficiency is required in a 6" deep filter. The Puracell II P & PH Series combines state-of-the-art mini-pleat construction techniques with superior reliability to offer maximum value for commercial and industrial applications. Additionally, the Puracell II P & PH Series offers unique advantages over the traditional 12" rigid box filter including lower freight costs, reduced storage area requirements and less impact on landfills. The Glasfloss Puracell II P & PH comes in a variety of standard sizes and efficiencies.

The Glasfloss Puracell II P & PH 6" filter is a mini-pleat cartridge encapsulated with a highimpact polystyrene plastic frame. An optional gasket can be applied to the filter frame. The Puracell II P & PH pack is pleated, wet laid micro fiber media. The pleats are separated and supported by a uniform glue bead that produces a low initial pressure drop while maximizing the filtration area. The media pack is resistant to moisture and does not support the growth of bacteria and mold. The media pack is thoroughly sealed to the inside of the plastic frame to prevent air bypass. The filter shall be rated to withstand temperatures up to 180 degrees Fahrenheit. The recommended final resistance for Puracell II P & PH filters is 1.5" w.g.



"Serving You With Locations Throughout The Nation"

Glasfloss has a policy of uninterrupted research, development and product improvement and reserves the right to change design and specifications without notice. www.glasfloss.com • (214) 741-7056 PRODUCT BULLETIN 11PURP&PH6 • SECTION 11 • 1-1-2024




PURACELL II P & PH 6" SERIES

MERV 15 / MERV 14												
BASE MODEL NUMBER		SIZE W x H x D NOMINAL		RATED VELOCITY FPM	INITIAL RESIST. IN. W.G. P PH			FINAL RESIST. IN. W.G.	MEDIA SQUARE FEET		SIZE W x H x D NOMINAL	
MERV 15	MERV 14				MERV 15	MERV 14	MERV 15	MERV 14		Р	РН	ММ
242469	242463	24 x 24 x 6	23-3/8" x 23-3/8" x 5-7/8"	500	0.58	0.44	0.65	0.51	1.50	139.85	121.56	610 x 610 x 152
*202569	*202563	20 x 25 x 6	19-3/8" x 24-3/8" x 5-7/8"	500	0.58	0.44	0.65	0.51	1.50	120.42	103.16	508 x 635 x 152
202469	202463	20 x 24 x 6	19-3/8" x 23-3/8" x 5-7/8"	500	0.58	0.44	0.65	0.51	1.50	116.07	98.28	508 x 610 x 152
202069	202063	20 x 20 x 6	19-3/8" x 19-3/8" x 5-7/8"	500	0.58	0.44	0.65	0.51	1.50	96.10	80.00	508 x 508 x 152
162569	162563	16 x 25 x 6	15-3/8" x 24-3/8" x 5-7/8"	500	0.58	0.44	0.65	0.51	1.50	95.40	79.58	406 x 635 x 152
162069	162063	16 x 20 x 6	15-3/8" x 19-3/8" x 5-7/8"	500	0.58	0.44	0.65	0.51	1.50	76.42	62.10	406 x 508 x 152
122469	122463	12 x 24 x 6	11-3/8" x 23-3/8" x 5-7/8"	500	0.58	0.44	0.65	0.51	1.50	67.13	53.02	305 x 610 x 152

	MERV 13 / MERV 11											
BASE MODEL NUMBER		SIZE W x H x D NOMINAL		RATED VELOCITY FPM	INITIAL RESIST. IN. W.G. P PH				FINAL RESIST. IN. W.G.			SIZE W x H x D NOMINAL
MERV 13	MERV 11				MERV 13	MERV 11	MERV 13	MERV 11		Р	РН	ММ
242462 *202562 202462 202062 162562 162062 122462	242461 *202561 202461 202061 162561 162061 122461	$\begin{array}{c} 24 x 24 x 6 \\ 20 x 25 x 6 \\ 20 x 24 x 6 \\ 20 x 20 x 6 \\ 16 x 25 x 6 \\ 16 x 20 x 6 \\ 12 x 24 x 6 \end{array}$	23-3/8" x 23-3/8" x 5-7/8" 19-3/8" x 24-3/8" x 5-7/8" 19-3/8" x 23-3/8" x 5-7/8" 19-3/8" x 19-3/8" x 5-7/8" 15-3/8" x 24-3/8" x 5-7/8" 15-3/8" x 19-3/8" x 5-7/8" 11-3/8" x 23-3/8" x 5-7/8"	500 500 500 500 500 500 500	0.42 0.42 0.42 0.42 0.42 0.42 0.42 0.42	0.32 0.32 0.32 0.32 0.32 0.32 0.32 0.32	0.49 0.49 0.49 0.49 0.49 0.49 0.49	$\begin{array}{c} 0.40\\ 0.40\\ 0.40\\ 0.40\\ 0.40\\ 0.40\\ 0.40\\ 0.40\\ 0.40\\ \end{array}$	$ \begin{array}{r} 1.50 \\ $	134.25 116.94 111.88 92.63 92.64 72.95 65.73	115.09 97.89 93.11 75.79 75.52 58.95 50.43	610 x 610 x 152 508 x 635 x 152 508 x 610 x 152 508 x 508 x 152 406 x 635 x 152 406 x 508 x 152 305 x 610 x 152

Tolerances shall be +/- 1/16" for width and height. Performance values based on ASHRAE and in-house testing methods. *Model Number Size Configuration may be produced as 20x25 or 25x20.

L7**Gla**



Glasfloss has a policy of uninterrupted research, development and product improvement and reserves the right to change design and specifications without notice.

www.glasfloss.com · (214) 741-7056