




Product Highlights


- MERV 10
- High Capacity
- Heavy-Duty Moisture Resistant Construction
- Galvanized Expanded Metal Backing
- Standard Size 4" and 6" Thick Incorporate Media Separators

Features

The Glasfloss® Z-Line® Series HV pleated filters offer improved performance for virtually every application. All Glasfloss® Z-Line® HV pleated filters feature fibers which do not absorb moisture and will not support microbial growth. The Z-Line® Series HV is ideal in high-velocity systems where maximum square footage of media is necessary.

Specifications

Glasfloss Z-Line® Series HV air filters shall be of the extended-surface pleated-media type. The media utilized shall be made of 100% synthetic fibers. The media shall be pleated in a tapered radial configuration. A heavy duty, recycled expanded metal reinforcement shall be laminated to the air-exit side of the media by a thermo-setting adhesive to maintain continuity of the radial pleats. The expanded metal shall be galvanized to resist rust and corrosion. The pleated cartridge shall be bonded to the peripheral interior of the outer frame. A heavy-duty moisture-resistant beverage board incorporating post-consumer material shall be utilized for an encasing frame. The frame face shall be internally laminated to the pleated cartridge apexes. Glasfloss Z-Line® Series HV filters shall be classified under U.L. std. 900 and shall be rated to withstand temperatures up to 180 degrees Fahrenheit. The Glasfloss Z-Line® Series HV filters achieve a MERV 10 rating per the ANSI/ASHRAE 52.2 Test Standard.



"Serving You With Locations Throughout The Nation"

Glasfloss has a policy of uninterrupted research, development and product improvement and reserves the right to change design and specifications without notice.

glasfloss.com · (214) 741-7056

PRODUCT BULLETIN 6ZLINEHV · SECTION 6 · 7/23/26

HV Standard Size Filters

SIZE W x H x D NOMINAL	SIZE W x H x D EXACT	RATED VELOCITY FPM	INITIAL RESIST. IN. W.G.	MEDIA SQUARE FOOT	SIZE W x H x D NOMINAL MM	RATED VELOCITY M/H	INITIAL RESIST. PASCALS
10 x 10 x 1	9-1/2 x 9-1/2 x 7/8	300	.18	1.61	254 x 254 x 26	5490	44.8
10 x 20 x 1	9-1/2 x 19-1/2 x 7/8	300	.18	2.67	254 x 508 x 26	5490	44.8
10 x 24 x 1	9-1/2 x 23-1/2 x 7/8	300	.18	3.22	254 x 610 x 26	5490	44.8
10 x 30 x 1	9-5/8 x 29-5/8 x 7/8	300	.18	4.95	254 x 762 x 26	5490	44.8
12 x 12 x 1	11-1/2 x 11 1/2 x 7/8	300	.18	2.06	305 x 305 x 26	5490	44.8
12 x 20 x 1	11-1/2 x 19-1/2 x 7/8	300	.18	3.29	305 x 508 x 26	5490	44.8
12 x 24 x 1	11-3/8 x 23-3/8 x 7/8	300	.18	3.96	305 x 610 x 26	5490	44.8
12 x 25 x 1	11-1/2 x 24-1/2 x 7/8	300	.18	4.13	305 x 635 x 26	5490	44.8
12 x 30 x 1	11-5/8 x 29-1/2 x 7/8	300	.18	5.16	305 x 762 x 26	5490	44.8
14 x 14 x 1	13-1/2 x 13-1/2 x 7/8	300	.18	3.12	356 x 356 x 26	5490	44.8
14 x 20 x 1	13-1/2 x 19-1/2 x 7/8	300	.18	3.91	356 x 508 x 26	5490	44.8
14 x 24 x 1	13 1/2 x 23 1/2 x 7/8	300	.18	4.70	356 x 610 x 26	5490	44.8
14 x 25 x 1	13-1/2 x 24-1/2 x 7/8	300	.18	4.90	356 x 635 x 26	5490	44.8
14 x 30 x 1	13 5/8 x 29 5/8 x 7/8	300	.18	6.56	356 x 762 x 26	5490	44.8
15 x 20 x 1	14-1/2 x 19-1/2 x 7/8	300	.18	4.11	381 x 508 x 26	5490	44.8
15 x 30-5/8 x 1	14-5/8 x 30-1/4 x 7/8	300	.18	10.57	381 x 777 x 26	5490	44.8
16 x 16 x 1	15-1/2 x 15-1/2 x 7/8	300	.18	3.45	406 x 406 x 26	5490	44.8
16 x 20 x 1	15-1/2 x 19-1/2 x 7/8	300	.18	4.32	406 x 508 x 26	5490	44.8
16 x 24 x 1	15-1/2 x 23-1/2 x 7/8	300	.18	5.20	406 x 610 x 26	5490	44.8
16 x 25 x 1	15-1/2 x 24-1/2 x 7/8	300	.18	5.41	406 x 635 x 26	5490	44.8
16 x 30 x 1	15-5/8 x 29-5/8 x 7/8	300	.18	6.67	406 x 762 x 26	5490	44.8
18 x 18 x 1	17-1/2 x 17-1/2 x 7/8	300	.18	4.44	457 x 457 x 26	5490	44.8
18 x 20 x 1	17-1/2 x 19-1/2 x 7/8	300	.18	4.94	457 x 508 x 26	5490	44.8
18 x 24 x 1	17-1/2 x 23-1/2 x 7/8	300	.18	5.94	457 x 610 x 26	5490	44.8
18 x 25 x 1	17-1/2 x 24-1/2 x 7/8	300	.18	6.19	457 x 635 x 26	5490	44.8
18 x 30 x 1	17-5/8 x 29-5/8 x 7/8	300	.18	8.23	457 x 762 x 26	5490	44.8
20 x 20 x 1	19-1/2 x 19-1/2 x 7/8	300	.18	5.55	508 x 508 x 26	5490	44.8
20 x 22 x 1	19-1/2 x 21-7/8 x 7/8	300	.18	6.15	508 x 558 x 26	5490	44.8
20 x 24 x 1	19-3/8 x 23-3/8 x 7/8	300	.18	6.68	508 x 610 x 26	5490	44.8
20 x 25 x 1	19-1/2 x 24-1/2 x 7/8	300	.18	6.96	508 x 635 x 26	5490	44.8
20 x 30 x 1	19-5/8 x 29-5/8 x 7/8	300	.18	8.23	508 x 762 x 26	5490	44.8
22 x 22 x 1	21-1/2 x 21-1/2 x 7/8	300	.18	7.17	558 x 558 x 26	5490	44.8
24 x 24 x 1	23-3/8 x 23-3/8 x 7/8	300	.18	7.92	610 x 610 x 26	5490	44.8
24 x 30 x 1	23-5/8 x 29-5/8 x 7/8	300	.18	9.90	610 x 762 x 26	5490	44.8
25 x 25 x 1	24-1/2 x 24-1/2 x 7/8	300	.18	8.51	635 x 635 x 26	5490	44.8
10 x 20 x 2	9-1/2 x 19-1/2 x 1-3/4	500	.27	6.24	254 x 508 x 51	9150	67.2
12 x 12 x 2	11-1/2 x 11-1/2 x 1-3/4	500	.27	4.33	305 x 305 x 51	9150	67.2
12 x 20 x 2	11-1/2 x 19-1/2 x 1-3/4	500	.27	7.20	305 x 508 x 51	9150	67.2
12 x 24 x 2	11-3/8 x 23-3/8 x 1-3/4	500	.27	8.66	305 x 610 x 51	9150	67.2
14 x 20 x 2	13-1/2 x 19-1/2 x 1-3/4	500	.27	8.64	356 x 508 x 51	9150	67.2
14 x 25 x 2	13-1/2 x 24-1/2 x 1-3/4	500	.27	10.83	356 x 635 x 51	9150	67.2
15 x 20 x 2	14-1/2 x 19-1/2 x 1-3/4	500	.27	9.12	381 x 508 x 51	9150	67.2
16 x 16 x 2	15-1/2 x 15-1/2 x 1-3/4	500	.27	7.66	406 x 406 x 51	9150	67.2
16 x 20 x 2	15-1/2 x 19-1/2 x 1-3/4	500	.27	9.60	406 x 508 x 51	9150	67.2
16 x 24 x 2	15-1/2 x 23-1/2 x 1-3/4	500	.27	11.55	406 x 610 x 51	9150	67.2
16 x 25 x 2	15-1/2 x 24-1/2 x 1-3/4	500	.27	12.03	406 x 635 x 51	9150	67.2
18 x 18 x 2	17-1/2 x 17-1/2 x 1-3/4	500	.27	9.92	457 x 457 x 51	9150	67.2
18 x 20 x 2	17-1/2 x 19-1/2 x 1-3/4	500	.27	11.04	457 x 508 x 51	9150	67.2
18 x 24 x 2	17-1/2 x 23-1/2 x 1-3/4	500	.27	13.28	457 x 610 x 51	9150	67.2
18 x 25 x 2	17-1/2 x 24-1/2 x 1-3/4	500	.27	13.84	457 x 635 x 51	9150	67.2
20 x 20 x 2	19-1/2 x 19-1/2 x 1-3/4	500	.27	12.00	508 x 508 x 51	9150	67.2
20 x 24 x 2	19-3/8 x 23-3/8 x 1-3/4	500	.27	14.43	508 x 610 x 51	9150	67.2
20 x 25 x 2	19-1/2 x 24-1/2 x 1-3/4	500	.27	15.04	508 x 635 x 51	9150	67.2
20 x 30 x 2	19-5/8 x 29-5/8 x 1-3/4	500	.27	18.24	508 x 762 x 51	9150	67.2
24 x 24 x 2	23-3/8 x 23-3/8 x 1-3/4	500	.27	17.61	610 x 610 x 51	9150	67.2
25 x 25 x 2	24-1/2 x 24-1/2 x 1-3/4	500	.27	18.65	635 x 635 x 51	9150	67.2
12 x 24 x 4	11-3/8 x 23-3/8 x 3-3/4	500	.22	13.61	457 x 610 x 102	9150	54.7

Tolerances shall be +/- 1/8" for height, width and +/- 1/16" for depth. Recommended final resistance is 1.00" w.g.
All special sizes will be undersized by 1/8" unless specified otherwise.

"Serving You With Locations Throughout The Nation"

Glasfloss has a policy of uninterrupted research, development and product improvement and reserves the right to change design and specifications without notice.
glasfloss.com · (214) 741-7056

HV Standard Size Filters

SIZE W x H x D NOMINAL	SIZE W x H x D EXACT	RATED VELOCITY FPM	INITIAL RESIST. IN. W.G.	MEDIA SQUARE FOOT	SIZE W x H x D NOMINAL MM	RATED VELOCITY M/H	INITIAL RESIST. PASCALS
16 x 20 x 4	15-1/2 x 19-1/2 x 3-3/4	500	.22	15.43	406 x 508 x 102	9150	54.7
16 x 25 x 4	15-1/2 x 24-1/2 x 3-3/4	500	.22	19.34	406 x 635 x 102	9150	54.7
18 x 24 x 4	17-1/2 x 23-1/2 x 3-3/4	500	.22	21.03	457 x 610 x 102	9150	54.7
20 x 20 x 4	19-1/2 x 19-1/2 x 3-3/4	500	.22	18.52	508 x 508 x 102	9150	54.7
20 x 24 x 4	19-3/8 x 23-3/8 x 3-3/4	500	.22	22.27	508 x 610 x 102	9150	54.7
20 x 25 x 4	19-1/2 x 24-1/2 x 3-3/4	500	.22	23.20	508 x 635 x 102	9150	54.7
24 x 24 x 4	23-3/8 x 23-3/8 x 3-3/4	500	.22	27.21	610 x 610 x 102	9150	54.7
12 x 24 x 6	11-3/8 x 23-3/8 x 5-3/4	500	.18	20.86	305 x 610 x 152	9150	44.8
16 x 20 x 6	15-1/2 x 19-1/2 x 5-3/4	500	.18	23.66	406 x 508 x 152	9150	44.8
16 x 25 x 6	15-1/2 x 24-1/2 x 5-3/4	500	.18	29.65	406 x 635 x 152	9150	44.8
18 x 24 x 6	17-1/2 x 23-1/2 x 5-3/4	500	.18	32.24	457 x 610 x 152	9150	44.8
20 x 20 x 6	19-1/2 x 19-1/2 x 5-3/4	500	.18	28.39	508 x 508 x 152	9150	44.8
20 x 24 x 6	19-3/8 x 23-3/8 x 5-3/4	500	.18	34.14	508 x 610 x 152	9150	44.8
20 x 25 x 6	19-1/2 x 24-1/2 x 5-3/4	500	.18	35.58	508 x 635 x 152	9150	44.8
24 x 24 x 6	23-3/8 x 23-3/8 x 5-3/4	500	.18	41.73	610 x 610 x 152	9150	44.8

Tolerances shall be +/- 1/8" for height, width and +/- 1/16" for depth. Recommended final resistance is 1.00" w.g.
All special sizes will be undersized by 1/8" unless specified otherwise.

Pleats Per Lineal Foot


DEPTH	HV
1"	16
2"	15
4"	11
6"	11

Media Area to Face Area Ratio

DEPTH	HV
1"	1.97
2"	4.40
4"	6.80

MINIMUM PARTICLE SIZE EFFICIENCY

Test Filter Size 24" x 24" x 2" Nominal




"Serving You With Locations Throughout The Nation"

Glasfloss has a policy of uninterrupted research, development and product improvement and reserves the right to change design and specifications without notice.
glasfloss.com · (214) 741-7056


STANDARD PRESSURE DROP

Test Filter Size 24" x 24" x 1" Nominal



STANDARD PRESSURE DROP

Test Filter Size 24" x 24" x 2" Nominal




Glasfloss Industries incorporates color-coded carton labels on standard sizes to help identify the product which enhances warehouse operations and shipments.



Glasfloss manufactures a variety of medium and high efficiency air filters which can be specified for LEED certification applications. For specific information on these products, please contact your local Glasfloss Sales Representative.



Distributed by:



"Serving You With Locations Throughout The Nation"